





"S"SERIES FILTER

Commercial strength polymer media filters

testament to the quality and reliability of Poolrite "S" Series

Features

- One piece seamless rotationally moulded
- Made from medium density polyethylene
- smooth even flow of water into the filter tank
- flow for fast and efficient backwashing which increases time between backwash cycles
- Australian design & manufacture

Warranty




Poolrite recommends using



Dimensions


S-5000






S-6000






S-8000





5-9000





POOLRITE

Specifications

MODEL	S-5000	S-6000	S-8000	S-9000
Filter Tank Diameter	522mm (20 in)	635mm (25 in)	770mm (30 in)	813mm (32 in)
Max Flow Rate (L/hr)	15,000	18,000	27,000	30,000
Diamond Kleen media M10 fine (kgs)	45	90	120	150
Diamond Kleen media M20 coarse (kgs)	30	45	45	60
Recommended Pump Model	SQI-400	SQI-500 / SQI-600	SQI-600	SQI-700

Designed to suit the award winning V2000 Multiport Valve

- 50mm ports and large diameter valve for greater water flow and quieter operation
- · Domed top cover to prevent debris building up around valve stem for easy operation and longevity
- 50mm plumbing unions allowing quick connection and simplified servicing with reducers to 40mm
- · Over moulded gaskets to prevent spider gasket blow outs





