

sunrain

TOP: Full-Inverter, Heating & Cooling, ABS casing, R32, COP up to 16

Features:

1. Fully Inverter with R32 gas. High-end Mitsubishi.
2. Heating & Cooling function.
3. DC Inverter Fan motor. Ultra quiet operation.
4. Hot gas defrosting.
5. Intelligent logic to offer constant pool temperature.
6. Electronic Expansion Valve



Model No.	BYC-007TV1	BYC-010TV1	BYC-013TV1	BYC-017TV1	BYC-021TV1	BYC-030TV1	BYC-035TV1	BYC-030TV3	BYC-035TV3
* Heating Capacity at Air 26°C, Humidity 80%, Water 26°C in, 28°C out									
Heating Capacity (kW)	7.2~1.7	9.2~2.3	12.5~3.0	16.5~3.8	21~4.8	28~6.8	35~8.8	28~6.8	35~8.8
Power Input (kW)	1.06~0.11	1.35~0.15	1.84~0.19	2.43~0.24	3.09~0.30	4.12~0.43	5.15~0.56	3.97~0.43	5.15~0.56
COP	15.8~6.8	15.8~6.8	16~6.8	15.8~6.8	15.8~6.8	15.8~6.8	15.8~6.8	15.8~6.8	15.8~6.8
* Heating Capacity at Air 15°C, Humidity 70%, Water 26°C in, 28°C out									
Heating Capacity (kW)	5.9~1.4	7.4~1.9	9.5~2.3	13.1~3	16.5~3.8	23~5.5	25.5~6.4	23~5.5	25.5~6.4
Power Input (kW)	1.2~0.18	1.51~0.25	1.9~0.30	2.67~0.39	3.37~0.5	4.7~0.72	5.2~0.84	4.7~0.72	5.2~0.84
COP	7.6~4.9	7.6~4.9	7.6~5	7.6~4.9	7.6~4.9	7.6~4.9	7.6~4.9	7.6~4.9	7.6~4.9
* Cooling Capacity at Air 35°C, Water 29°C in, 27°C out									
Cooling Capacity (kW)	4.2~1.0	5.3~1.3	7.2~1.7	9.4~2.1	11.6~2.7	14.9~3.8	19.3~4.9	14.9~3.8	19.3~4.9
Power Input (kW)	1.11~0.15	1.4~0.19	1.89~0.25	2.47~0.31	3.05~0.4	3.92~0.57	5.08~0.73	3.92~0.57	5.08~0.73
EER	6.6~3.8	6.7~3.8	6.7~3.8	6.7~3.8	6.7~3.8	6.7~3.8	6.7~3.8	6.7~3.8	6.7~3.8
* General data									
Power supply	220~240V/1/50						380~415V/3/50		
Max Power Input (kW)	1.45	1.75	2.2	2.5	3.2	4.45	6.43	4.76	6.93
Max Current (A)	7.1	8.3	10.2	11.9	14.7	20.4	30	7.9	11.3
Water Flow Volume (m ³ /h)	2.5	3.5	4.5	5.5	6.5	9	12	9	12
Refrigerant	R32								
Heat Exchanger	Titanium								
Air Flow Direction	vertical								
Kind of defrost	by 4 way valve								
Working temp. range (°C)	-15~43								
Casing Material	ABS								
Water Proof Level	IPX4								
Noise level 1m dB(A)	39~49	40~52	42~53	43~55	45~56	47~58	49~59	47~58	49~59
Noise level 10m dB(A)	20~29	20~32	22~33	23~35	25~36	27~38	29~39	27~38	29~39
Net Weight (kg)	44	46	55	57	61	86	92	86	92
Gross Weight (kg)	55	57	68	70	72	96	104	96	104
Net Dimensions (mm)	530*530*640		650*650*770			715*715*955			
Package Dimensions (mm)	560*600*780		680*720*910			765*785*1080			

Notes:

Warranty: 2 years for the whole unit, 5 years for compressor

Payment Terms: 30% in advance, 70% balance before delivery from Auckland