

R290 All In One Hot Water Heat Pump Water Heater

- * Built In 2kw Backup Electric Heater
- * 75°C Hot Water Max
- * 45db Low Noise
- * R290 Eco Friendly Refrigerant
- * Automatic Sterilization Function At 65°C
- * Wifi Control
- * Microchannel Heat Exchanger



Model	YT-200TD2	YT-270TD2
Power supply	220V~240V/50HZ	220V~240V/50HZ
Rated Input Power(Heat pump)	1200W	1200W
Rated Input Current(Heat pump)	5.3A	5.3A
Rated Heating Capacity(Heat pump)	2.78KW	2.78KW
Rated Input Power(Resistance)	1.8KW	1.8KW
Rated Input Current(Resistance)	7.5A	7.5A
COP (A 20/15, W 15-55)	4.15	4.15
Max Input Power(HP&Resistance)	3000W	3000W
Max Current(HP&Resistance)	14A	14A
Water Tank vlume	200L	270L
Hot Water Production rate	60L/H	60L/H
Refrigerant	R290 (400g)	R290 (400g)
Max Allowable Pressure	3.0MPa	3.0MPa
TPR valve	850KPa	850KPa
Working range with element	-15°C-43°C	-15°C-43°C
Working range without element	-7°C-43°C	-7°C-43°C
IP Class	IPX4	IPX4
Unpacked Dimension (outdoor unit)	φ620mm*1518mm	φ620mm*1838mm
Packed Dimension (outdoor unit)	700*700*1565mm	700*700*1880mm
Net Weight	104KG	118KG
Gross Weight	120KG	140KG
Noise	43dBA	43dBA

Notes:

Warranty: 2 years for the whole unit, 5 years for compressor

Delivery Time: 45 days to 60 days

Technical Date

